



SIDE VIEW

**FRONT VIEW
(CABLE IS NOT SHOWN)**

- NOTES:**
- 1). UPRIGHT CONFIGURATION SHALL BE USED FOR MOUNTING ON MAST ARMS, SIGNAL HEAD FRAMEWORKS AND PEDESTALS.
 - 2). UPRIGHT MOUNTING HARDWARE SHALL BE SUPPLIED BY THE DEPARTMENT.
 - 3). TEFLON TAPE SHALL BE APPLIED TO THREADS BEFORE MOUNTING.
 - 4). ROUTE THE LEAD-IN CABLE THROUGH THE METAL CAP AND THE RUBBER PLUG. REPLACE THE METAL CAP, SEALING THE CABLE ENTRY PORT. TIGHTEN THE METAL CAP SO THE CABLE WILL NOT SLIDE THROUGH THE RUBBER PLUG.

PLAN SYMBOL



**DELAWARE
DEPARTMENT OF TRANSPORTATION**

EMERGENCY PREEMPTION RECEIVER, UPRIGHT MOUNT

STANDARD NO. T-14 (2004) SHT. 1 OF 2

APPROVED *Carolann Wicks* 1/10/05
CHIEF ENGINEER DATE

RECOMMENDED *Dennis M. O'Flaherty* 1/13/05
DESIGN ENGINEER DATE